



ACC1300

FEATURES

- Convenient Wall Mount Design
- Ten (10) Standard Steps Of Attenuation
- For Use With 25V Or 70V Lines
- Low Insertion Loss
- Silver Plated Switch Contacts

SPECIFICATIONS

Application: Speaker distribution line volume control
 Attenuator Type: Auto transformer
 Power Rating: 10W
 Input Voltage: 25V or 70V
 Control Positions: 11 & Open Circuit
 Insertion Loss: < 0.5dB
 Mounting Plate: Single-gang brushed stainless steel

Dimensions:
 H: 4.5" (11.4 cm)
 W: 2.75" (7.0 cm)
 D: 2" (5.1 cm)
 Weight: 1 lb. (0.45 kg)
 Recommended Backbox:
 Standard, single-gang electrical box

Control Position	10	9	8	7	6	5	4	3	2	1	0	Unmarked
Nominal Attenuation	0	-3	-6	-9	-12	-15	-18	-21	-27	-33	<-70	(OC)*

*Open Circuit — this is a spare switch position between 0 and 10. Attenuation at this position is not defined.

DESCRIPTION

The Rauland Model ACC1300 Area Speaker Volume Control is designed to control the volume of either one or several speakers in a commonly wired group for up to 10 watts of total power. It provides 10 steps of attenuation plus an Open Circuit position, and is designed for use with either 25V or 70V lines.

Attenuation is accomplished in 6dB steps at positions 1 and 2, and in 3dB steps at positions 3 through 10. To prevent damage to the control, there is no stop between position "10" (Max) and "0" (Off). The unit features silver-plated switch contacts and a brushed stainless steel single-gang wall plate with black knob. The ACC1300 installs in a standard single-gang electrical box.

ASSOCIATED EQUIPMENT

Telecenter Communication Systems
 All 25 / 70V Horns and Speakers



Rauland is a Division of AMETEK, Inc.
 USA +1 800 752 7725
 Asia Pacific +65 64835750

www.rauland.com
 Mid East & Africa +20 122 2154016
 Europe +30 693 7501168
 Latin America +1 847 454 4203

Architect and Engineer (A&E) Specifications
 available online at customerconnection.rauland.com
 Specifications subject to change without notice.