Model: TCPVY — Single Call Switch with Privacy

TCPVY

Features

- Mounts in a standard single-gang electrical box
- Rugged design and construction
- Multi-purpose design works with Telecenter 1100, System 21, IV, V, VI, VoIP, and ICS

Specifications

Environmental Parameters:
Temp.: 32° F (0° C) to 122° F (50° C)
Rel. Humidity: 0 to 90% (non condensing)

Wiring Requirements: Two (2) conductors

Connector: Multi-conductor pig-tail

Maximum Distance (to line card): 2000 ft. (600 m.)

Backbox Requirements: Raco 674 single-gang or equal

Dimensions: H: 4½" (11.4 cm)
W: 2¾" (6.5 cm)
D: 2" (5.1 cm)

Weight: 2.5 oz. (7.1 g)

Description

The Rauland TCPVY Single Call Switch with Privacy is designed specifically for use with Rauland Telecenter systems. It features a high-impact Cycolac (UL94V-0 rated) faceplate finished in cool grey to match other Telecenter components. The TCPVY is designed for single-gang flush mounting either alone or in the single-gang opening of the TCSPKR module.

The TCPVY features one (1) latching privacy switch to disallow room monitoring as well as a single (1) normal call button. It is compatible with multiple Telecenter systems. "Normal" call-ins are placed by momentarily depressing the "Call" section of the toggle switch. The station is put into privacy by pressing the latching "Privacy" section of the toggle switch. Depending on the type of Telecenter system and its programming, call-ins may be cancelled directly from the TCPVY and/or upgraded from "Normal" to "Emergency" calls.

Associated Equipment

Telecenter ICS:
- **TCACM** – Audio and Control Module
- **TCSLM** – Station Line Module
- **ICS2SLMG2** – Station Line Module, global two (2)-channel
- **ICSRES** – Call Switch Conversion Resistor Pack

Telecenter 1100 System

Telecenter IV System

Telecenter V System

Telecenter VI System

Telecenter VoIP System

Telecenter System 21:
- **TC2114** – Station Line Card, four (4) conductor

TCSPKR – Universal Three (3)-gang Speaker Module

Architect and Engineer (A&E) Specifications available online at: customerconnection.rauland.com
Specifications subject to change without notice

©Copyright 2008 Rauland-Borg Corporation Printed in USA Rev 08/08

USA • 800-752-7725 • Fax 800-217-0977
Canada • 905-607-2335 • Fax 905-607-3554
www.rauland.com

Rauland-Borg Corporation